

①⑫

EUROPEAN PATENT APPLICATION

①⑪ Application number: 86200448.8

⑤① Int. Cl.4: **G02B 6/38**

①⑫ Date of filing: 25.05.83

③③ Priority: 05.06.82 GB 8216433

③④ Date of publication of application:
20.11.86 Bulletin 86/47

③⑤ Publication number of the original application in
accordance with Art.76 EPC: 0 096 511

③⑥ Designated Contracting States:
BE DE FR GB IT NL

⑦① Applicant: **AMP INCORPORATED**
P.O. Box 3608 449 Eisenhower Boulevard
Harrisburg Pennsylvania 17105(US)


⑦② Inventor: **ten Berge, Eduardus Franciscus**
Antonius
14 Hobbemaplein
NL-5151 SL Drunen(NL)

⑦③ Representative: **Gray, Robin Oliver et al**
BARON & WARREN 18 South End Kensington
London W8 5BU(GB)

⑤④ Connector for terminating an optical fibre.

⑤⑦ A connector comprises a tubular crimping sleeve (48) containing a resiliently deformable alignment body (49) having a central alignment passage (50) for optical fibres (43, 45) characterised in that the crimping sleeve (48) extends beyond the alignment body (49) at opposite ends and a support bushing (44, 51) having a central fibre passageway is disposed within each end of the sleeve (48) adjacent the alignment body (49), each support bushing (44, 51) having a peripheral recess (52, 53) within the sleeve (48) whereby on crimping the sleeve (48) about the alignment body (49) and the bushings (44, 51) the sleeve (48) may be indented (60, 61) into the recesses (52, 53) to secure the bushings (44, 51) in abutment with opposite ends of the alignment body (49) and the alignment body (49) under axial constraint.

The connector is particularly suited for use in conjunction with an optical fibre terminal as disclosed and claimed in EPA 0096511 and comprising a short optical fibre length (6) having a relatively rigid metal coating.



EP 0 201 944 A1

"CONNECTOR FOR TERMINATING AN OPTICAL FIBRE"

This invention relates to an optical fibre termination technique and product which is useful in the provision of releasable fibre optic connections.

It is known to terminate optical fibres by ferrule members at which optically flat exposed fibre ends may be formed to facilitate concentric seating in a bore of an alignment member adapted to be engaged by aligned optical fibre terminations at opposite ends, and thereby install a disconnectable optical fibre connection. Reference is made, for example, to AMP Incorporated US Patent Specification 3 999 837.

It has also been proposed by GTE Laboratories in Technology News EDN 20 August 1980, to provide a releasable two-part connector in each part of which a short length of optical fibre has one end centered in a bushing and the other end disposed in an elastomeric splice ferrule adapted to receive the end of an optical fibre in abutting relationship with the other end of the short fibre in a permanent connection. The arrangement is such that the bushings of the two parts are brought into engagement with the one ends of the short fibre lengths in aligned face-to-face abutting relationship at an interface between the bushings.

It has also been proposed to interconnect or splice optical fibres by aligning end portions in a bore of a deformable alignment member and to deform the member about the fibres to secure them in aligned juxtaposition.

It is an object to present an improved connector for terminating an optical fibre, and in particular, for use in accordance with the teachings of EP-A-8216433 from which the application is divided.

According to the invention of EP-A-8216433 a method of terminating an optical fibre comprises forming a short length of optical fibre with a relatively rigid metallic coating of uniform thickness comprising an initial thin electroless coating of uniform thickness and a further relatively thick electroplated coating of uniform thickness, forming ends of the coated length with optical surfaces, and splicing the coated length at one end to the end of a fibre to be terminated.

This enables a fibre to be terminated by means which can more readily be connected in the field than can a plain fibre.

Suitably, after forming the optical surfaces, part of the coating is removed over an end portion of the coated length to define a reduced diameter end portion which is spliced to the fibre to be terminated.

This facilitates alignment of the spliced ends of the coated length and the fibre to be terminated by matching the diameter of the spliced portions more closely.

A paper published in Solid State Technology of February 1974 by C.Y. Kuo of the Electro-Metallics Department of Englehard Industries Division of Englehard Minerals & Chemicals Corporation, Newark, New Jersey, entitled Electrical Applications of Thin-Films Produced by Metallo-Organic Deposition, discusses advantageous means whereby an initial thin coating may be obtained by electroless plating using the so-called MOD techniques.

After forming the metal coated fibre length with optical faces the coated fibre length, at least at one end, is suitably subject to a further plating operation to define an annular raised section around the optical face at that end, the other end being spliced to the fibre to be terminated. The raised section assists in protecting the optical face.

It has been found that a fibre core of 100 micron diameter may be coated with metal to an outer diameter of 500 micron concentric within 1 micron with the core.

In order to carry out the technique a substantial length of fibre may be formed with a uniform relatively rigid coating before being chopped into short lengths which are then formed with the optical surfaces. A multiplicity of chopped lengths are suitably mounted in spaced parallel relation in a holding fixture so that optical faces may be formed simultaneously on the multiplicity by conventional grinding and polishing techniques.

The invention of EP-A-83303028.1 includes an optical fibre terminal for carrying out the method of the invention, and which is characterised by a short length of optical fibre having a relatively rigid metallic coating of uniform thickness and formed then at opposite ends with optical surfaces and comprising an initial electroless coating of uniform thickness and a further relatively thick electroplated coating of uniform thickness.

Suitably the coating at one end portion is thick relative to that at the other end portion, defining at the other end portion a reduced diameter section for splicing to a fibre to be terminated.

In an embodiment the fibre is of diameter in the range of 50 to 125 micron and the coated fibre has an outer diameter of 500 micron concentric with the core to within 1 micron.

Suitably, at least at one end, the coated fibre length is formed with an annular raised section around the optical surface defined by an extension of the coating beyond the optical surface.

For forming the splice between the fibre to be terminated and the short fibre length there are available many known techniques and devices. If the splice is to be formed under factory or laboratory conditions, a fusion or welding technique is appropriate to give a low loss splice connection. However such splice joints require expensive tooling and skilled workmanship and are generally not suitable or economic for field application.

A suitable technique for field application is the crimp technique in which ends of the fibre to be terminated and of the short fibre length are aligned within an alignment bore of a deformable alignment body contained within a metal crimping sleeve. Crimping to effect radial compression of the sleeve secures the fibre ends in alignment.

As claimed in EPA-83303028.1 the coated fibre length and the fibre to be terminated may be aligned in a deformable alignment body having an alignment passageway in which the length and the fibre to be terminated are disposed end-to-end, the alignment body being contained within a metal crimping sleeve which is radially crimped resiliently to deform the alignment body about the abutted ends of the coated length and the fibre to be terminated, the coated length projecting from the alignment body at one end.

According to the present invention a connector for terminating an optical fibre comprising a tubular crimping sleeve containing a resiliently deformable alignment body having a central alignment passage for optical fibres is characterized in that the crimping sleeve extends beyond the alignment body at opposite ends and a support bushing having a central fibre passageway is disposed within each end of the sleeve adjacent the alignment body, each support bushing having a peripheral recess within the sleeve whereby on crimping the sleeve about the alignment body and the bushings the sleeve may be indented into the recesses to secure the bushings in abutment with opposite ends of the alignment body and the alignment body under axial constraint.

In use as claimed in EPA-83303028.1 the crimping sleeve extends beyond the alignment body at opposite ends around support bushings, one at each end, the bushings having axial passageways for the coated fibre and the terminated fibre, respectively and engaging and axially constraining opposite ends of the alignment member under compression, indentations in the crimping sleeve securing the support bushings against movement apart, and the coated fibre projecting from the associated support bushing. Preferably

the coated fibre has a relatively thick coating over that portion projecting from the alignment body and a relatively thin coating over that portion within the alignment body.

Suitably the alignment body is formed of material selected from the group comprising eutectic lead-tin alloy, super-plastic zinc, aluminium of grain size of the order of 30 micron, super-plastic aluminium having a grain size of the order of 5 micron, and EPDM rubber, and the bushings may be of malleable metal such as brass.

The invention also includes a female connector comprising a fibre optic splice according to the invention characterised in that the crimping sleeve at one end extends beyond the support bushings and a metallic coated short optical fibre length may be mounted in the fibre passageway of the bushing at that end, the coated fibre projecting on opposite sides of the bushing, one end extending coaxially into the sleeve extension and the other end extending into the alignment passageway of the alignment body, a resilient alignment member being mounted in the sleeve extension and having an alignment passageway embracing the end of the coated fibre within the sleeve, and having an alignment passageway portion extending away therefrom for reception of a complementary coated fibre.

An alignment member may be resilient, for example, folded from sheet metal to define an alignment passageway of lesser diameter than that of the fibre ends to be inserted but having resilient wall parts which may be sprung apart on insertion of the fibre ends.

For use in a connector housing the terminated fibre is suitably mounted in a spring loaded carrier having latching means for latching the carrier in the housing, and spring loading means arranged to be compressed on engagement of the connector housing with a complementary housing and to bias the projecting end of the coated fibre length axially towards a complementary aligned fibre end in a complementary housing through an intermediate alignment member.

Suitably the spring loading means is provided in only one of the connector housings.

The invention will now be described by way of example, with reference to the accompanying partly diagrammatic drawings, in which:-

Figure 1 is a fragmentary exploded view of a connector assembly for terminating a pair of optical fibres and releasably connecting the terminated ends;

Figure 2 is a perspective view to an enlarged scale of an intermediate short fibre length of

the assembly of Figure 1;

Figure 3 is a perspective exploded view of a crimp splice;

Figure 4 is a perspective view of the assembled splice of Figure 3;

Figure 5 is a sectional side elevation of a fibre optic termination suitable for assembly in a connector housing for mating with a complementary connector;

Figure 6 is a fragmentary sectional elevation of part of a multi-way connector housing for the termination of Figure 5;

Figure 7 is an end view of a spring form alignment member for use in a connector of the kind shown in Figures 5 and 6, or assembly of Figure 1;

Figure 8 is a sectional perspective view of a male contact;

Figure 9 is a view similar to that of Figure 8 of the male contact assembled into a male connector;

Figure 10 is a sectional perspective view of a female contact;

Figure 11 is a view similar to that of Figure 10, but viewed from the opposite side, assembled into a female connector.

In the arrangement of Figure 1, optical fibres 1 and 2 are arranged for insertion into rear ends of splice ferrules 3, 4 which are at their other ends are arranged to receive the rear, reduced diameter ends 5 of coated intermediate, short fibre lengths 6. The forward larger diameter ends of the coated fibre lengths 6 are axially insertable with a close fit into opposite ends of an alignment member having a through passageway within which the ends of the lengths 6 may abut.

The intermediate short fibre lengths 6 are, as shown in Figure 2, formed with a metallic coating which has been etched away at the rear end 5 to reduce the diameter to that of the fibre 1 to which it is to be spliced. As has been described above, both ends of the fibre length 6 are suitably formed with optical surface before the etching process.

The enlarged forward end of fibre 6 is of suitably controlled length so the position of the forward face may be accurately determined by location of its rear end.

The splice assembly of Figure 3 comprises a cylindrical crimping ferrule 8 adapted to contain a deformable alignment member 9 formed from a deformable plastics extrusion 10, folded up to define an axial through passageway, and radially extending voids for accommodating circumferential deformation of the plastics. In use, as shown in Figure 4, the member 9 is contained within the ferrule and the end of a fibre length 1 inserted axially from one end to abut the end of the reduced portions 5 of a short coated fibre length 6 before reducing the ferrule 8 by crimping to secure the ends in the splice. During crimping axial forces are suitably applied to opposite ends of the alignment member 9, by use of a suitable tool, to resist longitudinal extrusion of the alignment member 9, and axial movement of the fibre ends apart.

The splice of Figures 3 and 4 and its method of assembly, is more fully disclosed in and forms the subject of our European patent application EP 81306159.5, publication No. 0056196, published 21 July 1982.

In Figure 5, a coated fibre length 12, formed generally as shown in Figure 2, with an enlarged diameter forward portion 13 and a reduced diameter tail 14, is positioned with the tail 14 extending into the through passageway of a crimp-splice assembly 15. The assembly 15 comprises an outer metal crimping ferrule 16 containing a deformable member 17 having a through passageway 18 for reception of the tail 14, at one end, and an optical fibre to be terminated, at the other, to be secured by crimping the ferrule 16.

The ferrule 16, at its forward end has an extension 19 slidably received within a latch collar 20 having a latch 31 for latching the assembly in the housing of Figure 6 by engagement with a shoulder 22 in the passage 23 thereof. The forward end 24 of the ferrule presenting a shoulder for engaging housing abutment 25.

A forward extension 26 of the deformable plastics member 17, of reduced diameter, supports the rear end of the enlarged diameter portion 13 of the fibre length 12, and presents an annular space 27 within the ferrule extension 19, which receives a rear end of a metal sleeve 28 carrying a biasing spring 29 acting against the forward end of the collar 20 and biasing the sleeve 28 and with it the fibre portion 13 forwards. The fibre portion 13 projects through the sleeve 28 and forwardly into one end of an alignment member 30 having a through passageway 31 within which the fibre portion 13 is a close fit. The fibre portion terminates approxi-

mately mid-way through the passageway 31 to leave a residual passageway portion for receipt of a projecting fibre portion of a complementary connector, not shown.

After the assembly of Figure 5 has been spliced to an optical fibre at the crimp-splice assembly 15, it is inserted into the housing passageway of Figure 6, from left to right, to register the ferrule shoulder 24 with the housing shoulder 25, to engage the latch 21 with the abutment 22. The alignment member is assembled from the right of Figure 6 to abut the forward end of the sleeve 28 and receive the forward portion of the coated fibre 13 within its passageway 31.

A complementary connector is generally similar, but the alignment member is omitted, and suitably also the biasing spring. Thus a coated fibre length projects forwardly from a mating face of the complementary connector and on mating engagement of the two connectors the complementary coated fibre penetrates the residual passageway portion 31 of the alignment member, to abut the end of the fibre portion 13. Suitably the alignment bushing displaces the sleeve 28 to the left against the bias of the spring 29 to ensure that the abutted fibre ends are biased together by the spring force.

The alignment member 30 may be formed as shown in Figure 8 as a spring member folded from sheet metal to define an axial passageway 32 encompassed on three sides by an arcuate base 33 and a pair of arcuate spring arms 34, convex inwards to define the passageway 32 of generally triangular section for receiving the fibre portion 13 in a spring fit. Suitably, at opposite ends of the alignment member the base 33 and spring arms 34 are formed radially outwards of the passageway 32 to define flared entrance sections to facilitate axial insertion of the coated fibre ends.

The male optical fibre connector of Figure 8 comprises a short metal coated fibre length 41, corresponding to that shown in and described in connection with Figure 2, and for concise identification, hereinafter referred to as an optical needle. The optical needle 41 comprises a forward portion 42 of enlarged diameter compared to a rearward portion 43, the forward portion 42 being supported coaxially in and projecting forwardly from a support bushing 44, and the rearward portion 43 being spliced to axial alignment with the stripped forward end 45 of an optical fibre 46 extending from its cable covering 47.

The splice is formed generally as described with reference to Figures 3 and 4, but is further improved. The splice comprises an outer metal sleeve 48 containing in a middle portion an align-

ment member 49, generally of the form disclosed in Figure 3 and folded to define an axial through passageway 50 accommodating the rearward portion 43 of the optical needle 41 and the stripped forward end 45 of the optical fibre 46. The sleeve 48 extends forwardly and rearwardly beyond the alignment member 49, and in its forward extension, accommodates the support bushing 44 coaxially with the alignment member, and at its rearward extension, accommodates a fibre support bushing 51 in similar manner. The support bushings 44 and 51 abut forward and rearward ends of the alignment member 49 and adjacent the abutting ends are formed with respective external annular grooves 52 and 53 of generally V-form.

The fibre support bushing 51 has a rearward extension 54 of reduced diameter, surrounding the optical fibre 46 with an enlarged bore 55 progressively reducing at a convergent portion 56 to a reduced diameter portion 57 adjacent the alignment member 49.

The through passageway 50 defined by the folded alignment member 49 has flared entry portions 58, 59 at opposite ends, to facilitate entry of the optical needle portion 43 and the fibre 45 and suitably defined by chamfers on the ends of the folded sections of the alignment member 49.

The splice assembly is preassembled with the optical needle 41, and the optical fibre 46 arranged to enter the forward end 45 into the alignment member 49 substantially to abut the rearward end of the needle portion 43. The sleeve 48 is then crimped about the alignment member 49 to effect precise axial alignment between the fibre end 45 and the needle portion 43. Simultaneously the sleeve portion surrounding the support bushings 44 and 51 are similarly crimped and indented into the grooves 52 and 53 at annular indentations. This serves to exert an axial constraint against ends of the alignment member 49 during the crimping process, and also thereafter to protect against the effects of creep of the material of the alignment member and undesirable relaxation of its alignment function.

In forming the splice it has been found that the alignment member 49 should be of material having a fine grain size in the micron range, because rough grain size materials buckle the fibre during crimping by micro-bending causing undesirable transmission losses. Eutectic tin-lead alloy and so-called super-plastic zinc have been found acceptable for grain size but suffer from creep in use, particularly with temperature cycling. A more satisfactory material is aluminium having a grain size of about 30 micron which does not suffer substantially from creep. A further material is super-plastic

aluminium produced by the British Aluminium Company which has a grain size about 5 micron and is resistant to creep. Some rubbers form suitable materials and a rubber known as EPDM produced by the Dutch Company DSM, is suitable, having excellent resistance to creep. The bushings 44 and 51 are suitably of malleable metal, e.g. brass, and during crimping are urged axially inwards to exert axial constraint on the central alignment member 49. The indentation 60 serves to maintain that constraint after crimping to resist creep relaxation of the member 49.

The male connector of Figure 8 is suitably mounted, as shown in Figure 9, in a cylindrical housing body 62, supporting the splice sleeve 48 and at its rearward end having a screw fitted cable clamp 43 for clamping the optical fibre cable 47 to the connector. At its forward end the housing body 62 has an externally threaded extension 64 formed with a bore surrounding the forwardly projecting needle part 42 and adapted to receive a complementary female connector to be described in connection with Figures 10 and 11.

The complementary female connector as shown in Figure 10 is similarly formed to the male connector described in connection with Figure 8, but the forward end of the sleeve 48 is extended at 65 forwardly beyond the needle support bushing 44 by substantially twice the length of the projecting needle portion 42. The sleeve extension 65 encases a resilient alignment member 66, defining a through passageway receiving the projecting needle portion 42. The alignment member 66 comprises a cylinder rolled up from a sheet metal blank, pushed with apertures 67 to define three spring arms 68 extending between cylindrical end portion 69 of the member 66, the arms being bowed inwardly to define, at a centre section of the member a constricted passageway of lesser diameter than the fibre portion 42, when in a relaxed condition. The cylindrical end portions 69 fit closely within the sleeve extension 65, and the forward end of needle portion 42 is resiliently clamped between the arms 68, at a mid-point of the alignment member 65.

As an alternative to the metal alignment member 66, an alignment member of resilient elastomeric material may be formed in the manner of the alignment member 10 of the splice of Figure 3, presenting a through passageway of diameter less than the thickened portion 42 of the optical needle so that on insertion of the needle into the passageway, resilient deformation of the alignment member takes place.

As shown in Figure 11, the female connector is suitably mounted in housing body 70 surrounding the splice section of the sleeve 48, and having at its rearward end a screw fitted cable clamp 71 for the optical cable 47. At its forward end, surrounding the sleeve extension 65, the housing 70 is formed with a rotatable coupling sleeve 72, internally threaded and radially spaced from the sleeve extension 65 to receive the threaded forward end 64 of the male connector of Figure 10. A biasing spring 73 is mounted within the housing 70 to bias the sleeve 48 forward, and to accommodate rearward movement thereof when the male and female connectors are mated.

On mating of the connectors of Figures 9 and 11, the projecting needle portion 42 of the male connector is entered into the alignment member 66 to be resiliently gripped by the spring 68 and centered with the needle of the female connector. As the coupling spring 72 is tightened on to the threaded male connector portion 64, the forward needle portions 42 are drawn into abutment and the spring 73 slightly compressed.

25 Claims

1. A connector for terminating an optical fibre comprising a tubular crimping sleeve (48) containing a resiliently deformable alignment body (49) having a central alignment passage (50) for optical fibres - (43, 45) characterised in that the crimping sleeve - (48) extends beyond the alignment body (49) at opposite ends and a support bushing (44, 51) having a central fibre passageway is disposed within each end of the sleeve (48) adjacent the alignment body (49), each support bushing (44, 51) having a peripheral recess (52, 53) within the sleeve (48) whereby on crimping the sleeve (48) about the alignment body (49) and the bushings (44, 51) the sleeve (48) may be indented (60, 61) into the recesses (52, 53) to secure the bushings (44, 51) in abutment with opposite ends of the alignment body (49) and the alignment body (49) under axial constraint.

2. A connector as claimed in claim 1, characterised in that the alignment body (49) is formed of material selected from the group comprising eutectic lead-tin alloy, super plastic zinc, aluminium of grain size of the order of 30 micron, super plastic aluminium having a grain size of the order of 5 micron and EPDM rubber.

3. A connector as claimed in claim 1 or claim 2, characterised in that the support bushings (44, 51)

are of malleable metal such as brass.

4. A connector as claimed in any of claims 1 to 3, characterised in that the crimping sleeve (48) terminates adjacent the support bushing at one end whereby a coated optical fibre may be mounted in the fibre passageway of the support bushing (44) at that one end, the coated optical fibre (41) projecting on opposite sides of the support bushing (44), one end (42) extending externally of the splice beyond the bushing (44) and the crimping sleeve - (48) with the other (43) extending into the alignment passageway (50) of the alignment body (49).

5. A fibre optic female connector comprising a connector as claimed in any of claims 1 to 3, characterised in that the crimping sleeve (48) at

one end (65) extends beyond the support bushing whereby a coated optical fibre (42) may be mounted in the fibre passageway of that support bushing, the coated fibre (42) projecting on opposite sides of the support bushing, one end extending coaxially into the sleeve extension (65) and the other extending into the alignment passageway of the alignment body, and including a resilient alignment member (66) for mounting in the sleeve extension (65) and having an alignment passageway for embracing the end of the coated fibre (42) within the sleeve extension (65) the alignment member (66) resiliently engaging the coated fibre - (42) and having an alignment passageway portion extending away therefrom for reception of a complementary coated fibre.

20

25

30

35

40

45

50

55

7




FIG.1




FIG.2




FIG.3




FIG.4




FIG. 5




FIG. 6

FIG. 7







FIG. 8










FIG. 11



European Patent
Office

EUROPEAN SEARCH REPORT

Application number

EP 86 20 0448

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)
A	DE-A-2 531 994 (SIEMENS) * claims 1, 2; figure 1 *	1	G 02 B 6/38
A	US-A-3 768 146 (F.A. BRAUN et al.) * column 2, lines 40-52 *	2	
A	DE-A-2 507 158 (BICC) * page 2 middle *	2	
A	US-A-4 325 607 (W.J. CARLSEN) * column 6, line 33 - column 7, line 14 *	4, 5	
			TECHNICAL FIELDS SEARCHED (Int. Cl.4)
			G 02 B 6/38
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 23-07-1986	Examiner FUCHS R
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO Form 1503 03 82